

Product data, Troldtekt® screws

TROLDTEKT® SCREWS

Troldtekt screws have been specially developed for installing Troldtekt panels. Both screws with crosshead (PH2) and screws with Torx head (Torx 20) are Ø13 mm. Troldtekt screws are electrogalvanised and coated in colours that complement Troldtekt natural wood and natural grey panels as well as standard Troldtekt colours.

TROLDTEKT® SCREWS FOR WOOD AND STEEL

Max. 0.7 mm steel



| SIZE | HEAD | COLOUR |
|----------------|------|--|
| 4.2×45 mm, Ø13 | PH2 | Natural grey, natural wood, white 101, grey 202, black 207 |
| 4.2×55 mm, Ø13 | PH2 | Natural grey, natural wood, white 101, grey 202, black 207 |
| 4.2×70 mm, Ø13 | PH2 | Natural grey, natural wood, white 101 |
| 4.2×80 mm, Ø13 | PH2 | Natural grey, natural wood, white 101 |

TROLDTEKT® SCREWS FOR WOOD (WITH WASHER)

| SIZE | HEAD | COLOUR |
|----------------|---------|--------------|
| 3.9×45 mm, Ø13 | Torx 20 | Natural wood |

TROLDTEKT® SCREWS FOR STEEL

Max. 1.5 mm steel
Self-drilling, with drill-shaped point



| SIZE | HEAD | COLOUR |
|----------------|------|-------------------------|
| 4.2×50 mm, Ø13 | PH2 | Natural wood, white 101 |

QUANTITIES

| PANEL THICKNESS (mm) | PANEL LENGTH (mm) | SCREW DIMENSIONS For wood/steel (mm) | SCREW DIMENSIONS For steel (mm) | NO. OF SCREWS (per panel) | MAX. SPAN (mm) | NO. OF PH2 SCREWS (per pack) | NO. OF TORX SCREWS (per pack) |
|----------------------|-------------------|--------------------------------------|---------------------------------|---------------------------|----------------|------------------------------|-------------------------------|
| 25/43 | 600 | 3.9/4.2×45 | 4.2×50 | 4 | 600 | 100 | 250 |
| | 1200 | - | - | 6 | - | - | - |
| | 2000 | - | - | 10 | - | - | - |
| | 2400 | - | - | 10 | - | - | - |
| 35/53 | 600 | 4.2×55 | 4.2×50 | 4 | 600 | 100 | - |
| | 1200 | - | - | 6 | - | - | - |
| | 2000 | - | - | 10 | - | - | - |
| | 2400 | - | - | 10 | - | - | - |
| | 600 | 4.2×70 | | 4 | 600 | 100 | - |
| | 1200 | - | | 6 | - | - | - |
| | 2000 | - | | 10 | - | - | - |
| | 2400 | - | | 10 | - | - | - |
| | 600 | 4.2×80 | | 4 | 600 | 100 | - |
| | 1200 | - | | 6 | - | - | - |
| | 2000 | - | | 10 | - | - | - |
| | 2400 | - | | 10 | - | - | - |

PROPERTIES

DIMENSIONS

| | |
|----------------|----------------|
| Thickness (mm) | 3.9/4.2 |
| Length (mm) | 45/50/55/70/80 |

FINISH

| | |
|-------------------|--------------|
| Electrogalvanised | 18 µ plating |
| Coating | Paint |

CORROSION-RESISTANCE

Delivered as C4

APPLICATION

Troldtekt screws are suitable for indoor use. In very aggressive environments, we recommend screws with extra corrosion protection, C5.

Troldtekt A/S
Sletvej 2A
DK-8310 Tranbjerg J
Tel.: +45 8747 8100
Fax: +45 8747 8111
info@troldtekt.com
www.troldtekt.com